

BAC 55



| Features | BAC 55 |
|------------------------|----------------------------|
| Outer dimensions in mm | 600 W x 500 D x 580 H |
| Inner dimensions in mm | 415 W x 315 D x 410 H |
| Volume | 53 liters |
| K value | 0,39 W/m ² .K |
| Weight | 16 Kg |
| Insulation material | Expanded polyurethane foam |
| Material of the walls | Rotomoulded polyethylene |

Specifications and optional equipment



Technical features

- 1** Body and door made of one piece rotomoulded polyethylene. Insulation with CFC free expanded polyurethane foam.
- 5** One-piece EPDM tubular seal.
- 6** Label holder
- 10** Hinging from moulding and 115° lid opening.
- 11** Flush mounted and recessed fastener
- 13** Stackable Bac 55 with embossed bottom and lid from moulding.
- 15** Integrally moulded handles

Standard equipment

- B** Eutectic plate support

Optional equipment

- A** Eutectic plate TOP 55
- C** Dry ice drawer
- N** Castor base fitted with 2 fixed and 2 swivelling wheels ø 100 mm
- O** Castor base fitted with 2 fixed and 2 swivelling wheels ø 100 mm with brake
- P** Castor base fitted with 4 swivelling wheels ø 100 mm, 2 with brake.
- S** Silicone seal



CO2Air, Inc • Xactics, Inc
Exclusive distributor in Japan

Dry Ice Service Corporation

595-1 Tonodaicho Wakaba-ku,
Chiba city, Chiba 264-0036, Japan
TEL:+81-43-255-5640 FAX:+81-43-255-8780
E-mail:Shiozaki@dryice-service.co.jp
<http://dryice-service.co.jp/>