

ROLL 300 Dry Ice



Features	ROLL 300
Outer dimensions in mm	715 Wx 810 D x 1140 H
Inner dimensions in mm	556 Wx 635 D x 845 H
Volume	298 litres
K value	0,38 W/m ² .K
Weight	70 Kg
Insulation material	Expanded polyurethane foam
Material of the walls	Rotomoulded polyethylene

Specifications and optional equipment



Technical features

- 1 Body and door made of one piece rotomoulded polyethylene. Grooves on internal walls facilitate cold gas flow natural convection
- 2 Body/door hinging with 2 pins
- 3 1-point « Pélican » closing system, made of rustproof treated steel.
- 4 Rustproof treated steel frame, flush mounted, fitted with 2 fixed and 2 swivelling castors Ø 100 mm
- 5 One-piece silicone seal. Retracting door stop to keep door fixed open.
- 6 Label holder

Optional equipment

- F 2 brake wheels ø 100 mm
G 4 metal feet ø 60 mm



CO2Air, Inc • Xactics, Inc
Exclusive distributor in Japan

Dryice Service Corporation

595-1 Tonodaicho Wakaba - ku,
Chiba city, Chiba 264-0036, Japan

TEL:+81-43-255-5640 FAX:+81-43-255-8780

E-mail: Shiozaki@dryice-service.co.jp

<http://dryice-service.co.jp/>